

# Distributor Name

# CROMWELL®



EVERY PRODUCT, EVERY INDUSTRY, ONE SUPPLIER!™



## KENNEDY PROFESSIONAL Professional Ratchet Combination Spanners

Chrome vanadium steel with mirror polish finish, preventing oil and dirt from adhering to the spanner, making for easier cleaning and preventing rust. 72-teeth ratcheting system which needs only 5° movement to operate ratchet. Thin wall design for greater access. Conform to **ASME B107.6**.

### Set

#### 9 Piece Metric:

10, 11, 12, 13, 14, 15, 16, 17 and 19mm.

#### 7 Piece AF:

3/8", 7/16", 1/2", 9/16", 5/8", 11/16" and 3/4".



Number of Pieces	Weight each	Order Code	Price/1 RND
9 Metric	2560g	KEN-582-3990K	1295.8

## SHERWOOD QUALITY CUTTING TOOLS HSS-Co 5% TiN Coated Countersink Set - 90°

### 6 Piece Set

#### High Performance Multi Flute

Manufactured from HSS-E cobalt for deburring and chamfering. Straight shank, ground flute

90° angle. Manufactured to

**BS328 : Part 5 : 1983.**

Inclusive angle 90°.

**Sizes:** 6, 8, 10, 12.5, 16 and 20mm.

**6  
PIECES**



Number of Pieces	Inclusive Angle	Order Code	Price/1 RND
6	90°	-8990Y	2915.20

## DISO LED Torch

Super bright white LEDs. 100,000 hour LED life. Battery life up to 50 hours (continuous). Precision machined high strength aluminium alloy. Twist on/off. Corrosion resistant anodised finish. Water and impact resistant. Comes with wrist strap. All joints sealed with 'O' rings. Powder coated and superbly balanced to give many years service.



Never needs a replacement bulb

Model Number	Batteries Required	Length (mm)	Order Code	Price/1 RND
TAL010S	2 x AA	73	EDI-904-2550K	122.30

## SWISS+TECH HSS TiN Tipped Jobber Drill Sets

**HSS TiN-tip**

Bright body with TiN coating on working part.

For drilling in steel, cast steel alloyed and non-alloyed, grey cast iron, graphite and malleable cast iron.

Point angle: 118°.

**25  
PIECES**

Made to **BS 328, DIN 338.**

x 0.5mm



Number of Pieces	Order Code	Price/1 RND
25	SWT-125-9020A	2284.90

## KOBE Variable 2-Speed Impact Drill

### ABH14.4VET-2

Light weight and well-balanced - soft grip design. Integral horizontal level indicator, integral bit holder with No.2 crosspoint and 4.5mm flat bits. Heavy duty motor and gearbox.

**No load speed:** 0 - 350/0 - 1,150rpm.

**Blows per minute:** 0 - 14,950bpm.

**Maximum torque:** 27.5Nm.

**Battery:** 2x Ah NiCad.

**Drilling capacity:** steel 10mm, aluminium 13mm, wood 28mm, masonry 13mm.

**Battery:** KBE-280-5902A  
**Charger:** KBE-280-5903A

14.4V NI-CAD

27.5 Nm

v2+

1HR CHARGE



Model Number	Weight each	Order Code	Price/1 RND
ABH14.4VET-2	2.2kg	-0160K	2309.10

VARIABLE SPEED

